

# TurboShear™

# SHEAR INS

# POWER!

for Natural Roofing Slate



### Telescoping Drill Clamp

adjusts to fit corded or cordless drills, including compact Lithium-ion models.



### Easy Attachment:

Easily attaches to most corded or cordless drills including smaller Lithium-ion models.

## No. TSNS1

Drill Not Included.

### What to expect:

- Produces desirable hand-cut appearance in 4-8 mm natural roofing slate.
- Lightweight, compact and portable. • Easy one-hand control.
- Telescoping clamp fits large or small drill housing. • Blade and skid plate are replaceable on the job-site.

### Performance:



Straight Cuts



Angled Cuts



Curved Cuts



### Actual Image of Cut!

See for yourself. Expect a clean hand cut appearance in 4-8 mm natural roofing slate.

Catalog Number	Description	Cutting Capacity Natural Roofing Slate	Net Wt. oz. (g)	Net Wt. lbs. (kg)
TSNS1	TurboShear, Slate Cutting	4 - 8 mm	—	2.4 (1.11)
<b>Replacement Parts</b>				
TSDC	TurboShear Drill Clamp	—	8 (227)	—
TSCG	TurboShear Heavy-Duty Chuck Guard	—	—	.06 (0.03)
TSNS1RB	TurboShear Replacement Blades for TSNS1	—	—	—

# Malco®